UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
10/596,619	06/19/2006	Johan Nystrom	P18772US1	8482	
27045 7590 01/27/2010 ERICSSON INC.			EXAMINER		
6300 LEGACY			JAMA, ISAAK R		
M/S EVR 1-C-11 PLANO, TX 75024			ART UNIT	PAPER NUMBER	
			2617		
			MAIL DATE	DELIVERY MODE	
			01/27/2010	PAPER	

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary		Application No.	Applicant(s)				
		10/596,619	NYSTROM ET AL.				
		Examiner	Art Unit				
		ISAAK R. JAMA	2617				
Period fo	The MAILING DATE of this communication app or Reply	ears on the cover sheet with the c	orrespondence address				
WHIC - Exter after - If NC - Failu Any r	ORTENED STATUTORY PERIOD FOR REPLY CHEVER IS LONGER, FROM THE MAILING DANSIONS of time may be available under the provisions of 37 CFR 1.13 SIX (6) MONTHS from the mailing date of this communication. Operiod for reply is specified above, the maximum statutory period or to reply within the set or extended period for reply will, by statute, reply received by the Office later than three months after the mailing and patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be tim vill apply and will expire SIX (6) MONTHS from cause the application to become ABANDONE	lely filed the mailing date of this communication. (35 U.S.C. § 133).				
Status							
1)	Responsive to communication(s) filed on <u>09 O</u>	ctober 2009					
•	• • • • • • • • • • • • • • • • • • • •	action is non-final.					
3)	Since this application is in condition for allowar		secution as to the merits is				
٥,	closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.						
Dispositi	on of Claims						
4)🖂	4)⊠ Claim(s) <u>1-65</u> is/are pending in the application.						
·	4a) Of the above claim(s) <u>1-32</u> is/are withdrawn from consideration.						
	5) \boxtimes Claim(s) <u>65</u> is/are allowed.						
′=	6)⊠ Claim(s) <u>33-50 and 52-64</u> is/are rejected.						
· <u> </u>	Claim(s) <u>51</u> is/are objected to.						
· <u> </u>	Claim(s) are subject to restriction and/or	r election requirement.					
Applicati	on Papers						
9) The specification is objected to by the Examiner.							
· -	The drawing(s) filed on is/are: a) ☐ acce		Examiner.				
,_	Applicant may not request that any objection to the						
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).							
11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.							
Priority ι	ınder 35 U.S.C. § 119						
a)l	Acknowledgment is made of a claim for foreign All b) Some * c) None of: 1. Certified copies of the priority documents 2. Certified copies of the priority documents 3. Copies of the certified copies of the prior application from the International Bureau See the attached detailed Office action for a list	s have been received. s have been received in Application rity documents have been receive u (PCT Rule 17.2(a)).	on No ed in this National Stage				
2) Notic 3) Inform	t(s) te of References Cited (PTO-892) te of Draftsperson's Patent Drawing Review (PTO-948) mation Disclosure Statement(s) (PTO/SB/08) r No(s)/Mail Date 10/09/2009.	4) Interview Summary Paper No(s)/Mail Da 5) Notice of Informal P 6) Other:	ite				

DETAILED ACTION

Response to Arguments

Applicant's arguments filed 10/09/2009 have been fully considered but they are not persuasive. In regard to Applicant's argument that Naden failed to teach the computing of a plurality of reliability values for a plurality of symbols in the received digital communication and the transmitting of a digital communication that has the computed reliability values embedded therein to the second node, and that the Examiner cited Zhu and stated "Zhu teaches a method and apparatus for reducing signal degradation in a received signal, whereby a method of modifying the values of a plurality of digital filter coefficients for use by a digital filter which is a component of a relay station, the relay station successively receiving a first signal, modifying the first signal using the digital filter to form a second signal, and transmitting the second signal with amplification". First, the meaning of the word "reliability" as described in the dictionary is "dependability" or "accuracy", and in the Applicant's disclosure, there is no sufficient explanation of what these "reliability values" are.. In addition, the Applicant is referring to (1) "separable MAP "filters" for the decoding of product and concatenated codes" of J. Lodge et al. and (2) "On the interpretation of the APP Algorithm as an LLR filter" of I. Land et al. both of which are work done by others. Furthermore, Applicant discloses on page 3, paragraph 0027 that the Log-APP filter 612a can be interpreted as using the code structure to "amplify" the reliability and the more amplification there is the more reliable the symbols are up to a limit decided by the code parameters. In light of that, Zhu which in the same endeavor of Naden, and the instant Application is

Art Unit: 2617

introduced to show that the combination makes the claimed subject matter obvious. Zhu as indicated in the earlier office action teaches a method of modifying the values of a plurality of digital filters coefficients for use by a digital filter which is a component of a relay station, the relay station the relay station successively receiving a first signal, modifying the first signal using the digital filter to form a second signal, and transmitting the second signal with amplification, the method comprising: (i) interrupting said transmission of the second signal; (ii) deriving an estimate of said interference and storing the derived interference estimate; (iii) resuming said transmission of the second signal; and (iv) modifying said digital filter coefficients using said stored interference estimate and said second signal, to reduce the difference between said second signal and said master signal [Colum 2, lines 46-63]. And in regard to Applicant's argument that Kostusiak embeds only a single measurement in its transmitted signal, namely RSSI information; Applicant is reminded again that RSSI information is known to be the received signal strength indicator value and that Applicant's "reliability" values are unexplained in a way to differentiate it from another value such Kostusiak's RSSI. Therefore the earlier rejection stands.

Page 3

Claim Rejections - 35 USC § 103

2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

⁽a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Art Unit: 2617

3. Claims 33, 50, 52, 55, 57, 60 and 63 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Patent Number 7,184,703 (Naden et al.) in view of U.S. Patent Number 7,085,314 (Zhu et al.).

Page 4

4. Regarding claims 33, 50, 52, 55, 57, 60 and 63, Naden teaches a wireless relay based network, comprising: a first node [Figure 4, # 2, source]; at least one relay station [Figure 4, #s 12, 14 and 16, Relays 1, 2 and 3]; and a second node [Figure 4, # 4, destination]; wherein said first node communicates with said second node via said at least one relay station [Column 2, lines 44-46], wherein each relay station is operative to: receive a digital communication from said first node [Column 2, lines 36-**42]**. But Naden fails to explicitly teach computing a plurality of reliability values for a plurality of symbols in the received digital communication and the reliability information is transmitted to the second node. Zhu teaches a method and apparatus for reducing signal degradation in a received signal [Title], whereby a method of modifying the values of a plurality of digital filter coefficients for use by a digital filter which is a component of a relay station, the relay station successively receiving a first signal, modifying the first signal using the digital filter to form a second signal, and transmitting the second signal with amplification [Column 2, lines 36-42]. Therefore, it would have been obvious to a person of ordinary skill in the art at the time the invention was made to incorporate the method of Zhu into the relay system of Naden in order to reduce the deterioration of a transmitted signal.

Art Unit: 2617

5. Regarding claim 50, Naden further teaches that when one relay station transmits multiple digital communications at different times then said second node combines the transmitted digital communications [Figure 2, column 11, lines 5-20].

- 6. Regarding claim 57, Naden further teaches that the relay station is used in a wireless multi-hop network [Column 2, lines 28-32].
- 7. Claims 34, 36, 37, 53, 54, 61 and 62 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Patent Number 7,184,703 (Naden et al.) in view of U.S. Patent Number 7,085,314 (Zhu et al.) and further in view of U.S. Patent Number 7,236,591 (Sim).
- 8. Regarding claims 34, 54 and 62 Naden and Zhu teach the limitations of claims 33, 52 and 60 above. But Naden and Zhu fail to teach is the use of a maximum a posteriori (MAP) filter that computes reliability values for code symbols based on a code structure of the received digital communication. Sim teaches a method for performing turbo decoding in mobile communication systems whereby in order that the input code words iteratively pass through two convolutional decoders, the two convolutional decoders should have output values corresponding to soft decision values having a probability rate of "0" or "1," not hard decision values such as "0" or "1." To obtain such soft decision values, a Maximum a Posteriori (MAP) decoding method is used, in which a posteriori probability value of a data bit is calculated and the data bit is decoded to obtain the maximum posteriori probability value [Column 1, lines 32-40]. Therefore, it would have been obvious to a person of ordinary skill in the art at the time the invention

Art Unit: 2617

was made to incorporate the method of Sim into the combined system of Naden and Zhu in order to measure the likelihood that the received bit a soft bit, i.e. a 0 or 1.

- 9. Regarding claim 36, Naden and Zhu teach the limitations of claim 33, above. But Naden and Zhu fail to teach that each relay station performs the computing operation using a soft output channel decoder that computes reliability values for information symbols based on a code structure of the received digital communication. Sim teaches that in order to obtain soft decision values, a Maximum a Posteriori (MAP) decoding method has been suggested, in which a posteriori probability value of a data bit is calculated and the data bit is decoded [Column 1, lines 36-38]. Therefore, it would have been obvious to a person of ordinary skill in the art at the time the invention was made to incorporate the method of Sim into the combined system of Naden and Gilhousen in order to obtain the maximum posteriori probability value.
- 10. Regarding claims 37, 53 and 61, Naden and Zhu teach the limitations of claim 36, 52 and 60 above. But Naden and Zhu fail to teach a soft output channel decoder employs: a maximum a posteriori (MAP) algorithm; a soft output Viterbi algorithm (SOVA); a Log-MAP algorithm; or, a Max-LOG-MAP algorithm. Sim teaches that the primary decoding and the secondary decoding are iterated for a certain number of times using a Maximum a Posteriori (MAP) algorithm, so as to reduce the receiving error rate [Column 3, lines 24-27]. Therefore, it would have been obvious to a person of ordinary skill in the art at the time the invention was made to incorporate the method of Sim into the combined system of Naden and Zhu in order to obtain the logarithm of the ratio of the a posteriori probability of each bit.

Art Unit: 2617

11. Regarding claim 35, Naden further teaches that each MAP filter also filters the received digital communication and redistributes noise to unreliable parts in the transmitted digital communication [Column 3, lines 21-26; Naden discloses that the relay equipment selects from the plurality of signals they receive from source equipments those which are of the highest quality in terms of (SINR), (CINR) or RSS to relay to destination equipments thereby minimizing noise amplification].

- 12. Claims 38-43 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Patent Number 7,184,703 (Naden et al.) in view of U.S. Patent Number 7,085,314 (Zhu) and further in view of U.S. Patent Number 5,115,224 (Kostusiak et al.).
- 13. Regarding claims 38-43, Naden and Zhu teach the limitations of claim 33, above. But Naden and Zhu fail to teach that the computed reliability values are embedded in the transmitted digital communication. Kostusiak teaches a personal security system network whereby each receiving transceiver will transmit a relay signal, which combines (i.e. embeds) the emergency signal with additional received-signal-strength indication (RSSI) information [Column 3, lines 37-39]. Therefore, it would have been obvious to a person of ordinary skill in the art at the time the invention was made to incorporate the method of Kostusiak into the combined system of Naden and Zhu in order to ascertain how far the transmitting unit is from the receiving unit.
- 14. Claims 44-49, 58 and 59 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Patent Number 7,184,703 (Naden et al.) in view of U.S. Patent Number 7,085,314 (Zhu) and further in view of the Applicant's admitted prior art.

Art Unit: 2617

15. Regarding claims 44-49, Naden and Zhu teach the limitations of claim 33, above. But Naden and Zhu fail to teach that first node is: a base station; a mobile station; or, a relay station; second node is: a base station; a mobile station; or, a relay station; each relay station is: a base station; a mobile station; or, a stand alone relay station; that the received digital communication is: an uplink received digital communication; a downlink received digital communication; a base station peer-to-peer received digital communication; or, a mobile station peer-to-peer received digital communication, and that the transmitted digital communication is: an uplink transmitted digital communication; a downlink transmitted digital communication; a base station peer-topeer transmitted digital communication; or, a mobile station peer-to-peer transmitted digital communication. Applicant's admitted prior art discloses that relay based networks include one station (node A) that transmits information in coded and modulated digital communications to another station (node B) via one or more relay stations (RSs). The relay station can be part of a base station (BS), a mobile station (MS) or a stand-alone relay station. The nodes A and B can be a BS, a MS and/or a relay station. And, the digital communications could be either uplink communications (link from MS to BS), downlink communications (link from BS to MS), MS to MS communications or BS to BS communications [Page 1, paragraph 0004], and in regard to claim 49, the Applicant's admitted prior art teaches that when multiple relay stations each transmit the digital communication then said second node combines the transmitted digital communications [Figure 5; #s 506 (a) and (b) and 504, pages 1 &2, paragraph 0009]. In addition, and in regard to claim 58, the Applicant's admitted prior art teaches that the second link

Art Unit: 2617

generally has a larger bandwidth and uses a different air interface protocol than the first link [Page 1, paragraph 0008]. Therefore, it would have been obvious to a person of ordinary skill in the art at the time the invention was made to have that the relay based networks include one station that communicates with another via a relay that may be a mobile, a base station or an stand-alone repeater, and to have the receiving node combine multiple relay signals. And that the bandwidth allotted between the relay and the destination node is greater than the bandwidth between the transmitting node and the relay in order to accommodate any additional information that may be required by the receiving node.

- 16. Claims 56 and 64 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Patent Number 7,184,703 (Naden et al.) in view of U.S. Patent Number 7,085,314 (Zhu) and further in view of U.S. Patent Number 7,130,601 (Khorram).
- 17. Regarding claims 56 and 64, Naden and Zhu teach the limitations of claims 33, 52 and 60 above. But Naden and Zhu fail to teach that the computed reliability values are implicitly embedded in the coded/modulated digital communication transmitted to the second node. Khorram discloses a method for determining received signal strength in a direct conversion receiver whereby the RSSI value (reliability value) includes the amplitude modulation [Figures 4-7, Column 6, 63-65]. Therefore, it would have been obvious to a person of ordinary skill in the art at the time the invention was made to incorporate the method of Khorram into the combined system of Naden and Zhu in order to transmit a more robust signal to the receiving node.

Application/Control Number: 10/596,619 Page 10

Art Unit: 2617

Allowable Subject Matter

18. Claim 51 is objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

- 20. Claim 65 is allowed.
- 21. The prior art made of record and relied upon by the Examiner in the prosecution of this Application fails to teach or even suggest "when one relay station knows a channel response of a link between that relay station and said second node then that relay station is able to construct a transmitted digital communication which is coherently combined at said second node with a similar transmitted digital communication received from another relay station" which is recited in claims 51 and 65.

Conclusion

THIS ACTION IS MADE FINAL. Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

Application/Control Number: 10/596,619 Page 11

Art Unit: 2617

Any inquiry concerning this communication or earlier communications from the examiner should be directed to ISAAK R. JAMA whose telephone number is (571)270-5887. The examiner can normally be reached on Monday-Thursday; 4-10.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Lester G. Kincaid can be reached on (571) 272-7922. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/IRJ/

/LESTER KINCAID/

Supervisory Patent Examiner, Art Unit 2617